

iG9

RTK GNSS with IMU Tilt Compensation

iG9a

RTK GNSS without IMU Tilt Compensation

small, lightweight, rugged, reliable



GPS + GLONASS + Galileo + BeiDou + QZSS ·
Any-Mix-Fix · tracking fully enabled · MAXPro ·
336-tracking channels · 50Hz ·
tracks and utilizes Galileo BeiDou L2C L5 today ·
RTK UHF & Network reference station functionality



Bright sunlight readable OLED panel ·
keyboard for quick mode selection and full control



Dual Batteries ·
9-hour Operation · hot swappable



With (iG9) or without (iG9a) IMU tilt compensated shots ·
IMU + GPS track correction reduces fly-away points



Well connected:
4G · built-in hotspot / internet sharing ·
Wi-Fi · http · ftp ·
Bluetooth · USB · Serial ·
403-473 MHz TxRx 2-watt UHF modem




27 GB high speed static observation memory ·
iGage direct download and OPUS submittal ·
direct to RINEX logging



IP68 · water and dust proof ·
cast magnesium case ·
3.3 lbs. with batteries ·
2-year iGage warranty

iG9 & iG9a GNSS RTK Specifications

Price (MSRP) ⁵	Please call iGage: +1-801-412-0011 or check: www.iG9.xyz for current prices	
GNSS Engine	Trimble BD-990: fully enabled tracking, MAXPro, Maxwell 7, 50-Hz	
		
GNSS Measurements	336+ Channels, 8 constellations, All-in-View Tracking Standard, 50-Hz Rate GPS L1C/A, L2C, L2E, L5 GLONASS L1 C/A, L2 C/A, L3 CDMA ⁶ Galileo E1, E5A, E5B, E5AltBOC, E6 BeiDou B1, B2, B3 QZSS L1 C/A, L1 SAIF, L2C, L5, LEX IRNSS L5 SBAS L1 C/A, L5; WAAS, EGNOS, MSAS MSS Trimble RTX	
RTK Performance ¹	Horz 8 mm + 1 ppm (RMS 1-sigma)	Vert 15 mm + 1 ppm (RMS 1-sigma)
Static PP Performance ¹	Horz 2.5 mm + ½ ppm (RMS 1-sigma)	Vert 5 mm + ½ ppm (RMS 1-sigma)
SBAS Performance	Horz 0.3 m RMS with WAAS in the United States 0.5 m RMS with QZSS, EGNOS, GAGAN	
GNSS Antenna	NGS Calibration	
RTK Initialization ⁴	< 8 seconds, 99.9% reliability	
TFFF (time to first fix) ⁴	Signal Reacquisition < 2 seconds	(leaving full obstruction to clear sky)
	Warm Start < 30 seconds	(ephemeris and last position known)
	Cold Start < 45 seconds	(no ephemeris or known position)
RTK Tilt Compensation ⁷	iG9: 200 Hz, 0 to 60°, 10 mm + 0.7 mm / ° tilt; IMU based; Tilt Compensation not available on the iG9a	
Protocols	Input RTCM 2.1, 2.2, 2.3, 3.0, 3.1, 3.2, CMR, CMR+, sCMRx Output RTCM 2.3, RTCM 3, RTCM 3.2, CMR, CMR+, sCMRx NMEA 0183 GSV, AVR, RMC, HDT, VGK, VHD, ROT, GGK, GGA, GSA, ZDA, VTG, GST, PJT, PJK, BPQ, GLL, GRS, GBS HCN and RINEX output for GNSS raw data	
Network	Integrated 4G modem LTE (FDD): B1,B2,B3,B4,B5,B7,B8,B20; DC-HSPA+/HSPA+/HSPA/UMTS: B1, B2, B5, B8; EDGE/GPRS/GSM 850/900/1800/1900MHz. Wi-Fi AP, Data Collector Internet: NTRIP and DIP connections	
Communication	Wi-Fi: 802.11 b/g/n; fully configurable via Web Interface WWAN: Integrated GSM/GPRS modem: 4G, HSPA, EDGE, GPRS, GSM SERIAL: One RS232 High Speed Serial port (7-pin LEMO) USB: Standard High-Speed USB Type-C Connector, iG9 mounts as a thumb drive Bluetooth®: v4.1 Integrated multimode Class 2. iOS, Android, Windows Mobile and Windows compatible UHF: Internal 2-watt Transmit / Receive UHF modem: 403-473 MHz; TrimTalk, EOTT, SATEL Network: 6 TCP/UDP Clients, 4 TCP Server / NTRIP Caster	
Physical	Size: 6.3" x 5.9" diameter x 4.3" high; Weight: 2.86 lbs., 3.34 lbs. with batteries Operating temperature: -45°F to 165°F; Storage temperature: -65°F to 185°F Humidity: 100% condensation; Vibration: Mil-Std-810G Waterproof and dust proof: IP67 water-resistant to 1m for 30-minutes without extra caps or covers Cast AZ91D magnesium alloy, stainless 5/8" 11 TPI pole mount, double-seal gaskets Shock: survives a 3-meter drop to concrete; connectors mechanical + dust cover protected	
Display / Buttons	OLED 128x128 1.46" sunlight readable with Next, Enter buttons; SV, Correction, Data Recording, Power LEDs	
Electrical	Power consumption: 3.2 watts as a rover; single-handed battery exchange Lithium-Ion battery capacity: qty 2 x 3,400 mAh 7.4 V standard batteries, 50.3 Wh, hot-swappable Battery Life ² : UHF Rover 8h, GSM Rover 9h External Power: input accepts 9 to 28 VDC; heavy duty external power cable included with base kits	
Storage	32-GB Internal Flash: over 300-days storage at 1 Hz, 10-years with 5-second epochs ³ Unlimited expansion with external flash drive	
Data Collection Software	X-PAD, LandStar7, Carlson SurvCE / SurvPC V 6.06 thru 6.08, MicroSurvey FieldGenius	
Warranty	2-year iGage warranty; accessories 1-year; batteries 90-days	

¹ Precision and performance values assume a minimum of 9-satellites in multipath clear, EMI free, obstruction free environment with reasonable atmospheric conditions and satellite geometry. Network based solutions based on shortest actual baseline. Post-processed accuracy is dependent on baseline length and time-on-point, 24-hour observations may be required. Stable mounts and generally accepted survey practices are required for the highest order survey results.

² Battery life varies with temperature and battery age. An external power source is recommended for static occupations lasting longer than 8-hours and base operation longer than 4 hours. Elevated and extreme cold working or storage temperatures (> 85°F, < -20°F) hasten capacity loss.

³ Assuming 14-tracked satellites.

⁴ Initialization times assume reasonable baseline, constellation and number of SV's in a multipath and obstruction clear environment.

⁵ Price includes Ground shipping to most USA address when purchased from iGage.

⁶ There is no public GLONASS L3 CDMA or Galileo E6 ICD, receiver is not guaranteed to be fully compliant with this signal. The hardware of this product is designed for BeiDou B3 compatibility (trial version) and its firmware will be enhanced to fully support such new signals as soon as the officially published signal interface control documentation (ICD) becomes available.

⁷ An RTK Fix is required for tilt initialization and use. Evaluate suitability for use.

Prices, specifications and descriptions are subject to change without notice. Please call us for the latest information and a written quotation.

FCC ID SY4-A01020. An FCC license is required for UHF base operation.



+1-801-412-0011

iGage Mapping Corporation

1545 South 1100 East STE 1

Salt Lake City Utah 84105 USA

info@igage.com www.igage.com