

X91+ GNSS



KEY FEATURES

- *Embedded 220 channels GNSS core module GPS, GLONASS, Galileo and BeiDou*
- *Outstanding RTK initialization and centimeter level position accuracy*
- *Landstar or Carlson's SurvCE Field data collection software scale to your survey need*
- *Built-in GPRS modem and UHF data link*
- *Seamless interoperability with major GPS/GNSS manufacturers*
- *Small, lightweight and rugged design for demanding field work*

The CHC X91+ GNSS is a compact GNSS receiver designed for high accuracy and productivity - even in harsh environments. Powered by 220 channels GNSS core engine, the X91+ GNSS provides a cost-effective solution to any surveying project.

Easy-to-use, efficient and intuitive work flow, designed for advanced network RTK survey, compact and rugged, the X91+ is the perfect choice for demanding survey applications.

Fully Integrated

Built-in GNSS engine, antenna, UHF and GSM/GPRS modules, Bluetooth® communication in one single unit to make your everyday work simple.

Compact and lightweight

The size of 180 mm x 80 mm (3.1 in x 7.1 in) makes the X91+ only weights 1.35 kg (48 oz) with battery.

Optimized for Network RTK

Connection to GNSS RTK Networks is made easy and benefits from the unique X91+ auto-connect feature.

Compatibility

The X91+ RTCM compliance with major GPS brands allow a trouble-free integration into an existing pool of survey instrument.

Competitive and Reliable

By combining decades of positioning and surveying know-how, the X91+ GNSS is one of the most powerful GNSS RTK solutions, with no compromise with quality but at an affordable price for every surveyor.

Technical Specifications

GNSS characteristics

- 220 channels with simultaneously tracked satellite signals
 - GPS: L1C/A, L1C, L2C, L2E, L5
 - GLONASS: L1C/A, L1P, L2C/A, L2P, L3
 - SBAS: WAAS, EGNOS, MSAS
 - Galileo: E1, E5A, E5B (test)
 - BeiDou: B1, B2 (optional)
- Advanced multipath mitigation technology
- Low noise carrier phase measurement

Performance specifications⁽¹⁾

- Real Time Kinematics (RTK)
 - Horizontal: 8 mm + 1 ppm RMS
 - Vertical: 15 mm + 1 ppm RMS
 - Initialization time: typically < 10 s
 - Initialization reliability: typically > 99.9%
- Post Processing Static
 - Horizontal: 3 mm + 0.5 ppm RMS
 - Vertical: 5 mm + 0.5 ppm RMS
 - Baseline Length: ≤ 300 km

Communications

- 1x RS232 serial port
- 1x high speed USB
- Integrated GSM/GPRS modem
- Integrated Bluetooth® class 2
- CHC radio modem internal Rx: 430-450/450-470 MHz
- Optional radio modem⁽²⁾:
 - Internal Rx/Tx: 403-473 MHz
 - External Tx DL5: 1W - 20W adjustable
- Protocols:
 - RTCM2.1, RTCM2.3, RTCM3.0, CMR, CMR+ input and output
 - NMEA0183 output
 - RINEX and HCN outputs for GNSS raw data

- Data Storage:
 - 4 GB internal memory
 - GPS device mounts as a USB external hard drive

Physical

- Size (HxD): 80 x 180 mm (3.1 x 7.1 in)
- Weight: 1.35 kg with battery (48 oz)
- Operating temperature: -40 °C to +65 °C (-40°F to 149°F)
- Storage temperature: -40 °C to +75 °C (-40°F to 167°F)
- Humidity: 100% condensation
- Waterproof and dust proof: IP67 - protected from temporary immersion to depth of 1 meter, floats
- Shock: survives a 2-meter drop on to concrete

Electrical

- Power consumption: 2.6 W
- Li-ion battery capacity: 2200 mAh
- Battery life: Up to 6 hours typical
- External power input: 9-18 VDC

Software (optional)

- CHC's Landstar field data collection software
- Carlson's SurvCE field data collection software

(1) Accuracy and reliability specifications may be affected by multipath, satellite geometry and atmospheric conditions. Performances assume minimum of 5 satellites, follow up of recommended general GPS practices. (2) UHF type approvals are country specific.

Specifications are subject to change without notice.

© 2013 - Shanghai HuaCe Navigation Technology Ltd . All rights reserved. The Bluetooth® world mark and logos are owned by Bluetooth SIG, Inc. The CHC logo and CHC are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners – Rev. May 2013

CHC - Shanghai HuaCE Navigation Technology Ltd.
Building 35, n° 680 Guiping Road
200233 Shanghai – China

Tel : +86 21 542 60 273

Fax : +86 21 649 50 963

Email : sales@chcnv.com | www.chcnv.com